

## M A T E R I A L   S A F E T Y   D A T A   S H E E T

## I. IDENTIFICATION

MANUFACTURED BY: Van Sickle Paint Mfg Co  
 PO Box 82222  
 Lincoln, NE 68501

REVISED: 09/03/2009  
 PRINTED: 09/10/2009

24 Hour Emergency Telephone  
 CHEMTREC 1-800-424-9300

General Information:  
 Mon-Fri 8 AM - 5 PM  
 712-737-4993

TRADE NAME: EXTERIOR LATEX SATIN PASTEL BASE

MFG. PRODUCT NUMBER: 9403X

## II. HAZARDOUS INGREDIENTS

CAS #107-21-1	Ethylene Glycol	WT %:	1-5	Footnote: (1)
ACGIH TLV:	39.4 ppm TWA	ACGIH STEL:		
OSHA PEL:	50 ppm TWA	OSHA CEILING:	50 ppm	OSHA PEAK:
VAPOR PRESSURE:	.12mmHg@25C	LEL%:		
CAS #25265-77-4	Texanol	WT %:	1-5	Footnote: (1)
ACGIH TLV:	N.D.	ACGIH STEL:		
OSHA PEL:		OSHA CEILING:		OSHA PEAK:
VAPOR PRESSURE:	.013mbar@20C	LEL%:		

## WARNING MESSAGES:

- (1) Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Chronic exposure may cause damage to the central nervous system, respiratory system, lung, eye, skin, liver, gastrointestinal tract, spleen, kidneys, and blood.
- (2) See Section IX for reportable Hazardous Air Pollutants.

## III. PHYSICAL DATA

BOILING RANGE: 212° F

EVAPORATION RATE: \* slower than ether \*

PERCENT VOLATILE BY VOLUME: 62.29%

WEIGHT PER GALLON: 10.35 LBS

VAPOR DENSITY: \* trace amounts of organic vapors will be heavier than air \*

ACTUAL VOC (lb/gal): 0.54

EPA VOC (lb/gal): 1.23

EPA VOC (g/L): 147.40

## IV. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 200+° F 93+° C

LEL: Refer to Section II

FLAMMABILITY CLASSIFICATION: \* Not Regulated \*

HAZARD CLASSIFICATION: \*Not Regulated\*

EXTINGUISHING MEDIA: \*carbon dioxide, dry chemical, or fire foam\*

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers may explode when exposed to extreme heat. (Due to buildup of steam pressure.)

SPECIAL FIRE FIGHTING PROCEDURES: Use water to keep closed containers cool.

#### V. HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: See Section II.

EFFECTS OF OVREXPOSURE: Inhalation- High vapor concentrations may cause drowsiness and irritation.  
Eyes- Causes irritation.  
Skin- Prolonged or repeated contact may cause drying, cracking, or irritation.  
Ingestion- Expected to be a low ingestion hazard.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: consult physician

PRIMARY ROUTE(S) OF ENTRY: Skin and Inhalation

EMERGENCY AND FIRST AID PROCEDURES:

INHALATION: Remove to fresh air. Restore breathing. Treat symptomatically. Consult a physician.

EYES: Flush immediately with large amounts of water for at least 15 minutes. Talk to a physician for medical treatment.

SKIN: Wipe off with towel. Wash with soap and water. Remove contaminated clothing.

INGESTION: If swallowed, call a physician immediately. Remove stomach contents by gastric suction or induce vomiting only as directed by a medical personnel. Never give anything by mouth to an unconscious person.

#### VI. REACTIVITY DATA

STABILITY: \*stable\*

HAZARDOUS POLYMERIZATION: \*will not occur\*

INCOMPATIBILITY: \* unknown \*

HAZARDOUS DECOMPOSITION PRODUCTS: Fire, burning and welding may generate carbon monoxide.

CONDITIONS TO AVOID: Fire, burning, and welding.

#### VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition (flames, hot surfaces and electrical, static or frictional sparks). Avoid breathing vapors. Ventilate area. Use non-sparking tools. Remove with inert absorbant.

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations.

### VIII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: In confined areas of poor ventilation, use chemical cartridge respirator or self-contained breathing apparatus.

VENTILATION: Provide general dilution or local exhaust ventilation in volume and pattern to keep TLV and LEL of most hazardous ingredient in Section II, below acceptable limit.

PROTECTIVE GLOVES: None required except for prolonged contact.

EYE PROTECTION:

Splash proof eye goggles. In emergency situations, use eye goggles with a full face shield.

OTHER PROTECTIVE EQUIPMENT: \*none\*

HYGIENIC PRACTICES: See Section V

### IX. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Do not store near heat, sparks, or flame.

OTHER PRECAUTIONS: \* none \*

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants':

Ingredient	CAS #	Wt% of HAPS in product	Pounds HAPS/ Gal product
-----	-----	-----	-----
Ethylene Glycol	107-21-1	3.7 %	0.4

---